



Barco FLM HD20

Ultra silent, compact 20k Lumens HD Projector

Light Output	20,000 center lumen 19,000 ANSI lumens
Resolution	1,920 x 1,080 (native)
Brightness uniformity	> 90 % for the total screen
Contrast ratio	2100:1 (full field) – high contrast mode 2700:1 (full field)
Display	3-chip DLP HD (1920 x 1080 pixels, aspect ratio 16:9)
Convergence	Max allowed convergence drift is 0.5 pixel. This is checked on vertical and horizontal midlines only. Corners are not applicable for convergence error. This is measured with TLD 1.2 lens on axis.
Features	<ul style="list-style-type: none"> • Picture-in-picture • Seamless switching with effects • Standard light shutter • Rigging points • Carrying handle • High contrast mode • P7 color processing • internal warp module
Picture-in-picture	2 sources simultaneously
Inputs	<ul style="list-style-type: none"> • configurable 5 cable (BNC) • DVI • (HD)SDI (+ loop through) • DVI - HDCP
Outputs	HDSDI/ SDI loop out
Communication	<ul style="list-style-type: none"> • 1x RS-232C IN (D-9 connector) • 1x RS-232C OUT (D-9 connector) • 1x RS-232C IN (XLR connector) • 2x prop. protocol (RJ45 connector) • xlr and mini-jack for wired remote control
Compatibility	<ul style="list-style-type: none"> • All current video sources (PAL, SECAM, NTSC) in Composite, S-Video, Component or RGB formats • All current HDTV sources • All computer graphics formats from VGA, SVGA, XGA,

	<p>SXGA, full HD, UXGA to QXGA</p> <ul style="list-style-type: none"> • Most Macintosh computers • Electronic workstations with a resolution up to QXGA (2048 x 1536 pixels @ 60 Hz) • Most computer sources with a pixel clock up to 300 MHz • DVI sources up to DC2K (2048 x 1080)
Input source compatibility	max. input: up to QXGA (2048 x 1536)
Screen size	From 1 - 12m / 3 - 39ft. recommended
Scan Frequencies	pixel clock >162Mhz (up to QXGA @ 60Hz)
Network connection	10/100 base-T
On board display server	Ethernet control standard remote control projector over ethernet via Projector Toolset
Ambient Temperature	Max 40°C (104°F)
Lamp	3 KW Xenon Warranty universal lamphouse: 750 Hrs
Lens Shift	Vertical: -10% to +110% Horizontal: -30% to +30% (small differences exist per lens type, e.g. short throw lenses have less shift)
Lens encoders	On zoom and focus (with TLD lenses)
ScenergiX	Standard horizontal & vertical electronic edge blending
Dust filters	Dense, high quality microfilters, also available as spare kit
Noise Level	58 dBA (at 40°C)
Mains Voltage	200 - 240 V
Power consumption	3700 W (with universal lamp)
Power Dissipation	max 13,300BTU/h
Weight	99 kg (220 lbs)
Dimensions	WxLxH: 707 x 1025 x 548 mm (27.8 x 40.3 x 21.5 inch) incl. carrying handle + rigging points
Shipping Dimensions	Width: 92 cm Height: 95 cm Depth: 123 cm Floor Space: 1,1316 m ² Volume: 1,075020 m ³ Gross Weight: 161 kg
Safety Regulations	Compliant with UL1950 and EN60950
Electromagnetic Interference	complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A

Available at:  NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/

Order Information

Projector: R9004510
Spare lamp: R9854535
6-pack dust filters: R9454470
24-pack dust filters: R9454480
RGB HV module: R9854440
FLM/SLM adaptor plate: R9854490
FLM carry handle: R9854530
FLM flight case: R9854510