



## BenQ MP776ST DLP Projector

Native Resolution	XGA (1024 x 768)
Projection System	DLP™ technology by Texas Instruments®
Brightness	3500 ANSI lumens
Lamp	280W, 3000/4000 hours(Normal/Eco)
Contrast Ratio	2400:1
Weight	4.9 lbs (2.2 kg)
Noise Level	34 / 29 dB (Normal/Economic mode)
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)
Dimensions	11.4 x 3.7 x 10.9 inches (290 x 94 x 278.6 mm)
Image Size	61" to 300"
Throw Ratio	0.61:1
Zoom Ratio	Fixed
Lens	F=2.6, f=6.9 mm
Display Color	Full 16.7 million color palette
Aspect Ratio	4:3 Native, 16:9 Selectable
Horizontal Frequency	31 ~ 82 KHz
Vertical Scan Rate	48 ~ 86Hz
Projection Position	Front/Rear, Table/Ceiling
Input Terminals	<b>PC:</b> Analog RGB: D-sub 15 pin x 2(shared with Component) <b>A/V:</b> HDMI V1.3 x 1 S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 <b>Audio:</b> Stereo Mini Jack x 1 Audio L/R : RCA x 2
Output Terminals	<b>PC:</b> D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1 12V Trigger
Control Terminals	Serial Connector : RS232 9 pin x 1 RJ45 x 1
Speakers	5W x 2
Video Compatibility	NTSC, PAL, SECAM
Auto Switching Power Supply	90 to 264 VAC, 50/60 Hz
Power Consumption	390W, Standby < 1W

On-Screen Display Language	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Hungarian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (24 Languages)
Preset Modes/ Application Modes	Dynamic Mode sRGB Mode Presentation Mode Cinema Mode User 1 Mode User 2 Mode
Functions	BrilliantColor™ VIDI™ 3D Color Management Crestron LAN Control Auto Keystone Closed Captioning Digital Zoom (x2) Variable Audio Out Quick Cooling Quick Auto Search Blank Panel Key Lock Auto Off Security Password HDTV Compatible High Altitude Mode "Q?" Hot Key for FAQ 3D Ready Freeze
Accessories (Standard)	Quick start guide Manual CD Remote control w/battery VGA cable PWR cord
Accessories (Optional)	Presentation Plus RS232 Cable Spare Lamp Kit (P/N: 5J.J0405.001) Soft Carry Case

Available at:  NETWORK Spectrum®

Call: 301-733-0657

Email: [sales@networkspectrum.com](mailto:sales@networkspectrum.com)

Other products available at:

[www.networkspectrum.com/gsaschedule/](http://www.networkspectrum.com/gsaschedule/)