



## BenQ MP777 DLP Projector

Native Resolution	XGA (1024 x 768)
Projection System	DLPTM technology by Texas Instruments®
Brightness	4000 ANSI lumens
Lamp	280W, 3000/4000 hours (Normal/Economic mode)
Contrast Ratio	2600:1 (Full on/Full off)
Weight	3.5 kg (7.7 lbs)
Noise Level	34/29 dB (Normal/Economic mode)
Resolution Support	VGA(640 x 350) to UXGA(1600 x 1200)
Dimensions	290 x 94 x 252 mm (11.4 x 3.7 x 9.9 inch)
Image Size	25" to 300"
Throw Ratio	1.51~1.96 (65"@2M)
Zoom Ratio	Manual Zoom, 1.3:1
Lens	F=2.56
Display Color	Full 16.7 million color palette
Aspect Ratio	4:3 Native, 16:9 Selectable
Keystone Adjustment	Auto Keystone Vertical $\pm$ 40 Degree; Manual Vertical $\pm$ 40 Degree
Horizontal Frequency	31-93 kHz
Vertical Scan Rate	48-86 Hz
Input Terminals	<b>PC:</b> Analog RGB: D-sub 15 pin x 2 <b>A/V:</b> HDMI V1.3 x 1 S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 <b>Audio:</b> Stereo Mini Jack x 1 Audio L/R : RCA x 2
Output Terminals	<b>PC:</b> D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1 12V Trigger
Speakers	5W x 2
Control Terminals	Serial Connector : RS232 x 1 RJ45 x 1
Video Compatibility	NTSC, PAL, SECAM
Auto Switching Power Supply	100 to 240 VAC, 50 to 60 Hz
Power Consumption	425W, Standby<1W

On-Screen Display Language	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Hungarian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (24 Languages)
Preset Modes/ Application Modes	Dynamic Mode sRGB Mode Presentation Mode Cinema Mode User 1 Mode User 2 Mode
Functions	BrilliantColor™ VIDI™ 3D Color Management Crestron LAN Control Auto Keystone Closed Captioning Digital Zoom (x2) Variable Audio Out Quick Cooling Quick Auto Search Blank Panel Key Lock Auto Off Security Password HDTV Compatible High Altitude Mode "Q?" Hot Key for FAQ 3D Ready Freeze
Accessories (Standard)	Quick Start Guide Manual CD Remote Control w/battery VGA Cable Power Cord Soft carry case
Accessories (Optional)	Ceiling Mounting Kit (P/N: 5J.J2K01.001) Spare Lamp Kit (P/N: 5J.J0405.001) Presentation Plus (P/N: 5J.J9301.001) RS232 Cable

Available at:  NETWORK Spectrum®

Call: 301-733-0657

Email: [sales@networkspectrum.com](mailto:sales@networkspectrum.com)

Other products available at:

[www.networkspectrum.com/gsaschedule/](http://www.networkspectrum.com/gsaschedule/)