



BenQ SP920P DLP Projector

Native Resolution	XGA (1024 x 768)
Projection System	DLP® technology by Texas Instruments®
Brightness	6000 ANSI lumens
Lamp	260W x2, 2000/3000 hours (Normal/Economic mode)
Contrast Ratio	2000:1 (Full on/Full off)
Weight	11 kg (24 lbs)
Noise Level	37/34 dB (Normal/Eco)
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)
Dimensions	443 x 167 x 355 mm (17.4 x 6.6 x 14 inch)
Image Size	31" to 300"
Throw Ratio	1.64 to 1.89
Zoom Ratio	Manual Zoom, 1.15:1
Lens	F=2.4~2.7 , f=38.87~46.63mm
Display Color	Full 16.7 million color palette
Aspect Ratio	4:3 Native, 16:9 Selectable
Horizontal Frequency	31-82 kHz
Vertical Scan Rate	48-85 Hz
Input Terminals	PC : Analog RGB: D-sub 15 pin x 1 AV: HDMI(v1.3)x1 Component video: RCA x3 S-Video: Mini Din 4 pin x 1 Composite video: RCA x 1 DVI-D(Support HDCP)x1 Audio: Stereo mini jack x 1
Output Terminals	PC: 12V Trigger D-sub (15 pin) X 1
Speakers	5 Watt Speaker x 2
Control Terminals	Serial Connector : RS232 8 pin MINI DIN USB Connector : USB x 1 (Type mini B) Wired Remote jack x 1
Video Compatibility	NTSC, PAL, SECAM
Auto Switching Power Supply	100 to 240 VAC, 50 to 60 Hz
Power Consumption	Max. 805W
On-Screen Display Language	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/

	Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai/ Polish
Preset Modes/ Application Modes	PC Input: Dynamic Mode Presentation Mode sRGB Mode Cinema Mode User 1 Mode User 2 Mode A/V Input: Dynamic Mode Standard Mode Cinema Mode User 1 Mode User 2 Mode
Functions	Dual lamp (3 sets of lamp mode) 3D Color Management Quick Auto Search Sleep Timer Presentation Timer Power On/Off Ring Tone Panel Key Lock Resolution Reminder 11 sets of Picture Mode "Q?" Hot Key for FAQ Freeze Lamp Care Wall Color Correction Brilliant Color™ VIDITM Blank (ECO mode) Quick Cooling Auto Off Security Password My Screen HDMI(v1.3) HDCP compatible HDTV compatible 12V trigger High altitude mode
Accessories (Standard)	User's Manual Quick Start Guide Manual CD Remote control Batteries for R/C VGA cable Power Cord
Accessories (Optional)	Ceiling Mounting Kit (P/N: 5J.J2K01.001) Presentation Plus (P/N: 5J.J9301.001) Spare Lamp Kit (Lamp#1 P/N: 5J.J2D05.001; Lamp#2 P/N: 5J.J2D05.011) RS232 Cable

Available at:  NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/