

8791HW

ImagePro 8791HW Portable LCD Projector



The ImagePro 8791HW is a light (5 lbs), easy-to-use portable LCD projector ideal for classroom or conference room.

8791HW FEATURES

- 2600 Lumens Brightness
- WXGA (1280x800) Resolution
- Lamp access on top
- High performance Hybrid filter with easy side access
- Short throw distance
- New 3000/4000 hour lamp
- Built-in Anti-theft security
- Audio "passthrough" permits use of sound system to play CDs on the PC when projector is off
- Super reliable operation



**NEW SIDE-LOADING FILTER PROVIDES
EASY FILTER MAINTENANCE**

THE ALL NEW
DUKANE
Education. Presentation. Inspiration.

Available at: **NETWORK Spectrum®**

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:
www.networkspectrum.com/gsaschedule/

Toll-free: 888-245-1966 • Web: www.dukane.com/av
Fax: 630-584-5156 • E-mail: avsales@dukane.com

ImagePro 8791HW Portable LCD projector

Back Panel

Connections



Key features:

- WXGA (1280 x 800) resolution
- 2600 ANSI lumens of brightness
- Whiteboard & Blackboard Modes
- Easy maintenance in ceiling mount with lamp access on top and Hybrid filter with side access
- Monitor loopthrough
- Instant On and Off
- Short throw distance
- Audio passthrough for sound when projector is off
- 3000/4000 hour lamp life
- Lock slot, security bar and transition detector
- Five Year Warranty and One Year Peace of Mind Service

8791HW Projection Table

Image Size 16:10		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	25.5	3.2	3.7
60	51.0	6.4	7.4
80	68.0	8.5	9.9
100	85.0	10.6	12.4
120	102.0	12.7	14.8
150	127.5	15.9	18.6
200	170.0	21.2	24.8
300	255.0	31.9	37.2

Throw Ratio (distance to width) 1.5 to 1.75

THE ALL NEW
DUKANE
Education. Presentation. Inspiration.

Audio Visual Products
2900 Dukane Drive
St. Charles, Illinois 60174
Toll-free: 888-245-1966
Fax: 630-584-5156
E-mail: avsales@dukane.com
Web: www.dukane.com/av

ImagePro is a registered trademark of Dukane Corporation



Specifications

Image Element	0.59" polysilicon active-matrix TFT x3
Brightness	2600 ANSI lumens (2100 lumens in Whisper Mode)
Resolution	1280 x 800 pixels (H X V), WXGA
Contrast	500:1
Scanning Frequency	fh 15 -106 kHz, fv 50-120 Hz
Lens	Manual zoom 1.2X
Lens Throw Ratio (16:10)	1.5 -1.75:1 throw distance to image width
Keystone Correction	Digital, vertical +/-30 deg
Aspect Ratio	16:10 Native, 4:3, selectable
Computer	SVGA, VGA, XGA, WXGA, SXGA, UXGA
Compatibility	MAC16"
Video Compatibility	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, Component Video, HDTV (1080i/p, 720p, 576i, 480i/p)
Image Control	Freeze function, electronic magnification and pan
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	200W UHB
Lamp Life	3000 hours (typical) 4000 hours (whisper mode)
Audio Output	1 watt
Throw Distance	36" to 455"
Screen Size, diagonal	30" to 300"
Inputs, Video	(1) Component, Share with RGB (1) Composite video, RCA x 1 (1) S-Video, mini DIN 4-pin (1) HDMI
Inputs, Computer	(1) RGB, 15 pin D-sub, component
Inputs, Audio	(2) Stereo mini jack
Outputs, Audio	(1) Stereo mini jack, adjustable level
Outputs, Monitor	RGB, 15 pin D-sub
Control	9 pin, D-sub, RS-232
Security	Kensington lock slot & Security Bar
Fan Level	35dB, ultra quiet; 29dB Whisper Mode
Closed Caption	For NTSC only
Operating Temperature	41-95 deg F
Power	AC 100-120V, AC 220-240V 50/60 Hz, 330 watt
Size (WxHxD)	12" x 3.0" x 8.7"
Weight	5 lbs.
Shipping Weight	15 lbs.
Carton Size	15" x 8" x 19" (est.)
Accessories Included	Remote control, batteries, power cord, RGB cable, operation manual
Safety Agency	UL/C-UL, FCC Class B, CE, ROHS
Optional Accessories	Lamp 456-8789H Ceiling Mount, Universal; RPM-U Filter: UX36761

Five (5) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

Specifications subject to change without notice.

5YR