


8959H-RJ

ImagePro 8959H-RJ Advanced, Versatile LCD Projector



Features – Special University Feature Group

- 5000 Lumens Brightness
- XGA Resolution
- Lamp access on top
- High performance (5000 HR) hybrid filter with easy access
- Special 16 Watt audio output
- New Microphone Input
- New 3000/5000 hour lamp
- Built-in Anti-theft security
- Audio "passthrough" permits use of the sound system even when projector is off
- Network (LAN) Control, Maintenance and security
- 0.5 Watt Power Saving Standby Mode
- PC less presentations from a memory card or the network
- HDMI Input
- Zoom range lens of 1.7x

THE ALL NEW
DUKANE
Education. Presentation. Inspiration.

Available at: **NETWORK Spectrum®**

Call: 301-733-0657

Email: sales@networkspectrum.com


Other products available at:
www.networkspectrum.com/gsaschedule/

Toll-free: 888-245-1966 • Web: www.dukane.com/av
Fax: 630-584-5156 • E-mail: avsales@dukane.com

ImagePro 8959H-RJ Portable LCD projector

Back Panel

Connections



Key features:

- XGA (1024 x 768) resolution
- 4000 ANSI lumens of brightness
- Stackable for two times the light output
- HDMI input
- Easy maintenance in ceiling mount with lamp access on top & 5000 hour filter with front access
- Horizontal and Vertical lens shift
- Monitor loophthrough & remote mouse control
- Microphone Input with amplifier
- PC less operation vis USB memory device
- 2000:1 Contrast
- Audio passthrough for sound when projector is off
- 16 Watt audio output
- 3000/5000 hour lamp life
- Lock slot, security bar and transition detector
- Five Year Warranty and One Year Peace of Mind Service

8959H-RJ Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	24	2.8	4.8
60	48	5.9	9.8
80	64	7.9	13.1
100	80	9.9	16.5
120	96	11.9	19.8
150	120	15.0	24.8
200	160	20.0	33.1
300	240	30.0	49.7

Throw Ratio (distance to width) 1.5 to 2.5



Audio Visual Products
2900 Dukane Drive
St. Charles, Illinois 60174
Toll-free: 888-245-1966
Fax: 630-584-5156
E-mail: avsales@dukane.com
Web: www.dukane.com/av



ImagePro is a registered trademark of Dukane Corporation

#10-00037-00

Specifications

Image Element	0.63" polysilicon active-matrix TFT x3
Brightness	5000 ANSI lumens (4200 lumens in Eco Mode)
Resolution	1024 x 768 pixels (H X V), XGA
Contrast	2,000 : 1 Active iris
Scanning Frequency	fh 15 -106 kHz, fv 50-120 Hz
Lens	Manual zoom (F1.6 - 2.1), 1.7X
Lens Throw Ratio	1.5 - 2.5:1 throw distance to image width
Keystone Correction	Digital, vertical and horizontal +/- 40 deg.
Aspect Ratio	4:3, 16:9 selectable
Computer	SVGA, VGA, XGA, SXGA, UXGA
Compatibility	MAC13" and MAC16"
Video Compatibility	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, Component Video, HDTV (1080i/p, 720p, 576i, 480i/p)
Image Control	Freeze function, electronic magnification and pan
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
PC less presentations	USB-A storage device slot
Lamp	245W UHP
Lamp Life	3000 hours (typical) 5000 hours (Eco mode)
Audio Output	2 speakers 16 watt combined
Throw Distance	35" to 597"
Screen Size, diagonal	30" to 300"
Inputs, Video	(1) Component, RCA x 3 (share w RGB) (1) S-video, Mini DIN 4-pin (1) Composite video, RCA x 1
Inputs, Computer	(1) RGB, 15 pin D-sub (1) RGB, BNCx5
Input Digital	(1) HDMI
Inputs, Audio	(2) Stereo mini jack: for PC 1&2 (1) RCA x 2 (for video)
Input from Mic	3.5mm Mini Audio
Outputs, Audio	(1) RCA x 2, adjustable
Outputs, Monitor	RGB, 15 pin D-sub
Outputs, Control	RS-232, 9 pin D-sub USB Type B (Mouse control)
Remote Control	3.5mm Mini Stereo
LAN Network Operation	RJ-45
Security	Kensington lock slot & Security Bar
Fan Level	35dB, ultra quiet; 29dB Eco Mode
Closed Caption	CCI, CC2, CC3, CC4, T1,T2,T3,T4
Operating Temperature	41-95 deg F
Power	AC 100-120V, AC 220-240V 50/60 Hz, 330 watt, >1W standby
Size (WxHxD)	15.7" x 4.1" x 12.5"
Weight	10.1 lbs.
Shipping Weight	16 lbs.
Carton Size	19" x 8" x 15"
Accessories Included	Remote control, batteries, power cord, RGB cable, operators manual, CD
Safety	UL/C-UL, FCC Class B
Optional Accessories	Lamp 456-8959H Ceiling Mount, Universal; RPM-U Filter; MU06641

Five (5) year limited warranty on parts and labor in North America, lamp is 90 day warranty (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

Specifications subject to change without notice.

