



Closed Captioning



AMX Device Discovery



Crestron Integrated Partner

Key Features

- Short Throw 36" for 80" screen
- 2,000 ANSI lumens
- 4,000 hour Hybrid Filter
- Template function
- MyScreen
- Input source naming
- Transition Detector
- Audio pass Through
- Power saving mode
- Blackboard whiteboard mode
- Security Bar
- Quick on/Direct off



Specifications

Model Name	CP-D10 Series	
Liquid Crystal Panel Structure	0.55" polysilicon active-matrix TFT x 3	
Number of Pixels	786,432 pixels	
Resolution	Video	540 TV lines
	RGB	1024 dots X 768 lines
Colors	16.7 million colors	
Aspect Ratio	Native 4:3/16:9 compatible	
Lens	Digital Zoom x 1.3	
Throw Ratio (distance : width)	0.6 (Fixed)	
Lamp	180W UHB	
Brightness	2,000 ANSI Lumens	
Expected lamp Life	Approximately 3,000 hours (normal) 4,000 hours (eco)	
Contrast Ratio	400 : 1	
Speaker Output	1W	
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz	
Power Consumption	250W	
Operating Temperature	5°C - 35°C (41°F - 95°F)	
Input Signals	RGB	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, MAC 16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
	Component Video	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Acoustic Noise Level	37 dB (29 dB in Eco Mode)	
H-Sync	15 kHz - 106 kHz	
V-Sync	50 kHz - 120 kHz	
Vertical Keystone	+ / - 5°	
Approvals	UL, C-UL, FCC, CE, RoHS	
RGB Input	Analog RGB	15pin Mini-Dsub x 2
RGB Output	RGB	15pin Mini-Dsub x 1
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	Shared with VGA 15pin D-Sub
Audio	Input	Stereo Mini jack x 2, RCA(L/R) x 1 pair
	Output	RCA(L/R) x 1 pair
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)	
Dimensions (W x D x H)	13.1" x 11.9" x 4.1"	
Weight	7.7 lbs.	
Additional Features	MyScreen, My Memory, My Button, My Text, My Source, Blackboard/ Whiteboard Mode, Day Time Mode, Input Source Naming(English), Resolution Setting, Template, Closed Caption, Audio Pass Through	
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label	
Lamp	CPD10LAMP (DT01091)	
Remote Control	HL02483 (Optional RC-R008 with laser pointer)	
Filter	UX35971	

Screen Size 4:3 Throw Distance

Diagonal*	Width*	Distance*
60	48	27
63	50	28
70	56	32
77	62	35
80	64	36
90	72	41
100	80	46

Throw Ratio: 0.6:1 (distance : width)

*Measured in inches



Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/