



Closed Captioning



AMX Device Discovery

Key Features

- 2,200 ANSI Lumens
- Native XGA Resolution
- 4.8 lbs.
- PIN Lock Security
- Whiteboard/Blackboard Mode
- 28 dB (Eco Mode)
- Front Air Exhaust
- Blank Button on Top
- Easily Replace Lamp from Top
- Air Filter on Side
- Easily Accessible High Efficiency Filter
- Instant On/Off
- 4,000 Hour Lamp Life (Eco Mode)
- Template Function
- Power Saving Mode
- Audio Pass Through
- Closed Caption
- Automatic Eco Mode



Specifications

Model Name	CP-RX82 Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	540 TV lines
Video	1024 dots X 768 lines
RGB	16.7 million colors
Colors	Native 4:3/16:9 compatible
Aspect Ratio	Manual zoom (F=1.7 ~ 1.9, f=19-23mm), Manual Focus
Lens	1.5 - 1.8 : 1
Throw Ratio (distance : width)	200W UHP
Lamp	2,200 ANSI Lumens
Brightness	2,200 ANSI Lumens
Color Light Output	Approximately 3,000 hours (normal) 4,000 hours (Eco Mode)
Expected lamp Life	500 : 1
Contrast Ratio	1W
Speaker Output	AC100 - 120V / AC220 - 240V 50/60 Hz
Power Supply	330W
Power Consumption	5°C - 35°C (41°F - 95°F)
Operating Temperature	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, MAC 16"
Input Signals	RGB
	Composite Video
	Component Video
Acoustic Noise Level	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
H-Sync	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
V-Sync	35 dB (28 dB in Eco Mode)
Vertical Keystone	15 Hz - 106 Hz
Approvals	50 Hz - 120 Hz
	+ / - 30°
RGB Input	Analog RGB
RGB Output	RGB
Video Input	S-Video
	Composite Video
	Component Video
Audio	Input
	Output
Dimensions (W x D x H)	12.0" x 8.7" x 3.0"
Weight	5.0 lbs.
Additional Features	My Screen, My Memory, My Button, My Text, My Source, Blackboard/ Whiteboard Mode, Daytime Mode, Input Source Naming(English), Resolution Setting, Template, Closed Caption(for NTSC only), Audio Pass Through
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label
Lamp	CPRX82LAMP (DT01151)
Remote Control	HL02771
Filter	MU06961

Screen Size 4:3 Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	35	42
60	48	71	85
80	64	95	114
100	80	119	143
120	96	143	171
150	120	179	215
200	160	238	286
300	240	358	430

Throw Ratio: 1.3 - 1.8:1 (distance : width)

*Measured in inches

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

For sales information, please call 800.225.1741

Printed 08.10



Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/