



AMX Device Discovery



Closed Captioning



Crestron Integrated Partner

Key Features

- 2,200 ANSI Lumens
- Native XGA Resolution
- 500:1 Contrast Ratio
- 7.9 lbs.
- Microphone input with amplifier
- Network control, maintenance and security
- Network Bridge RS232 control
- Lamp life approximately 6,000 Hours (Eco Mode)*
- HDMI / Component / Composite / S-Video Inputs
- Stand-by Audio
- 16W Speaker Output
- 0.5 watt power saving mode using 120V
- Template Function
- 2 RGB In, 1 RGB out / Composite / S-Video
- USB connection to computer
- PC-less presentation
- Network Messenger
- Present content via LAN
- 29 dB (Eco Mode)
- Stand-by Audio



Specifications



Model Name	CP-X2011N Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	540 TV lines
Video	1024 dots X 768 lines
RGB	16.7 million colors
Colors	Native 4:3/16:9 compatible
Aspect Ratio	manual zoom x 1.2
Lens	1.5 - 1.8 : 1
Throw Ratio (distance : width)	190W UHB
Lamp	2,200 ANSI Lumens
Brightness	Approximately 3,000 hours (normal) 6,000 hours (Eco mode)*
Expected lamp Life	500 : 1
Contrast Ratio	16W (2 x 8W speakers)
Speaker Output	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Supply	330W
Power Consumption	5°C - 35°C (41°F - 95°F)
Operating Temperature	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC 13", MAC 16"
Input Signals	RGB
	Composite Video
	Component Video
Acoustic Noise Level	480i, 576i, 480p, 720p, 1080i, 1080p
H-Sync	35 dB (29 dB in Eco Mode)
V-Sync	15 Hz - 106 Hz
Vertical Keystone	50 kHz - 120 kHz
Approvals	+ / - 30°
	UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB
RGB Output	RGB
Digital Input	
Video Input	S-Video
	Composite Video
	Component Video
Audio	Input
	Output
Ethernet	RJ-45 port / 100 base-T
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Other	USB-A, USB-B (USB Mouse)
Dimensions (W x D x H)	12.5" x 3.9" x 11.3"
Weight	7.9 lbs.
Closed Caption	CC1, CC2, CC3, CC4. T1, T2, T3, T4
Additional Features	Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard More, Input Source Naming., MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual
Lamp	CPX2010LAMP (DT01021)
Remote Control	HL02483
Filter	MU06481

Screen Size 4:3 Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	83
80	64	94	112
100	80	118	140
120	96	142	168
150	120	177	211
200	160	237	281
300	240	356	422



Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/