



AMX Device Discovery



Closed Captioning



Crestron Integrated Partner

## Key Features

- 3,200 ANSI Lumens
- Native XGA Resolution
- 2000:1 Contrast Ratio Using Active IRIS
- 8.2 lbs.
- Easily accessible hybrid filter (5,000 hours between maintenance)
- Lamp life approximately 6,000 Hours (Eco Mode)\*
- Audio Pass Through
- 16W Speaker Output
- 0.5 watt power saving mode using 120V
- Template Function
- 2 RGB In, 1 RGB out / Composite / S-Video
- Instant On/Off
- Security Bar / Transition Detector
- 29 dB (Eco Mode)



## Specifications



Model Name	CP-X3011 Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	540 TV lines
Video	1024 dots X 768 lines
RGB	16.7 million colors
Colors	Native 4:3/16:9 compatible
Aspect Ratio	manual zoom x 1.2
Lens	1.5 - 1.8 : 1
Throw Ratio (distance : width)	210W UHB
Lamp	3,200 ANSI Lumens
Brightness	Approximately 3,000 hours (normal) 6,000 hours (Eco mode)*
Expected lamp Life	2000 : 1 using Active Iris
Contrast Ratio	16W (2 x 8W speakers)
Speaker Output	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Supply	330W
Power Consumption	5°C - 35°C (41°F - 95°F)
Operating Temperature	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC 13", MAC 16"
Input Signals	RGB
Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
Component Video	480i, 576i, 480p, 720p, 1080i, 1080p
Acoustic Noise Level	35 dB (29 dB in Eco Mode)
H-Sync	15 Hz - 106 Hz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 30°
Approvals	UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB
RGB Output	RGB
Video Input	S-Video
Composite Video	15pin Mini-Dsub x 2
Component Video	15pin Mini-Dsub x 1
Audio	Input
Ethernet	Output
Control Terminals	Other
Other	Mini DIN 4-pin connector x 1
Dimensions (W x D x H)	RCA jack x 1
Weight	RCA jack x 3
Closed Caption	3.5 Stereo Mini jack
Additional Features	Output
Supplied Accessories	RCA(L/R) x 1 pair
Lamp	9-pin D-sub connector x 1 (RS-232 control)
Remote Control	USB connector (USB mouse) x 1
Filter	12.5" x 3.9" x 11.3"
	8.2 lbs.
	CC1, CC2, CC3, CC4, T1, T2, T3, T4
	Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard More, Input Source Naming, MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side
	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual
	CPX2010LAMP (DT01021)
	HL02483
	MU06481

Screen Size 4:3      Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	83
80	64	94	112
100	80	118	140
120	96	142	168
150	120	177	211
200	160	237	281
300	240	356	422

Throw Ratio: 1.5 - 1.8:1 (distance : width)



Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/