

2011 VIERA® U30 Series LCD

Available Model:
TC-L42U30



IPS PANEL

Delivers a 178° wide viewing angle for bright and clear images from virtually anywhere in the room.

120 HZ MOTION PICTURE PRO 4

Sports and fast action stay crisp and focused, with minimal motion blur.

VIERA IMAGE VIEWER

View your digital photos on your VIERA HDTV.

FINE BLACK PANEL

Reduces panel reflection to sharpen images and decrease glare.

-
- 1080p Full HD Resolution
 - Game Mode
 - VIERA Link™
 - 3 HDMI
 - PC Input
 - 24p Smooth Film



Panasonic
ideas for life

VIERA

2011 VIERA® U30 Series LCD

TC-L42U30		
VIDEO		
Screen Size Diagonal (in)	42.0	
Aspect Ratio	16:9	
Panel	IPS LCD 1080p (WSXGA)	
Filter	Fine Black Panel	
Number of Pixels	2,073,600 (1,920 x 1,080)	
Moving Picture Resolution	900 lines	
Viewing Angle	178 degrees	
HDTV Display Capability (1080p, 1080i, 720p)	Y	
EDTV Display Capability (480p)	Y	
Aspect Control	480i/ p: FULL, JUST, 4:3, ZOOM 1080i/ p: FULL, H-FILL, JUST, 4:3, ZOOM	
Progressive Scan	Y	
Panel Drive	120 Hz	
24p Smooth Film	Y	
24p Playback	Y	
x.v.Color	—	
Intelligent Scene Controller	Y	
Motion Focus Technology	Y	
Super Resolution	Y	
FULL HD 3D		
3D Panel	—	
3D 24p Smooth Film	—	
2D-3D Conversion	—	
3D Image Viewer	—	
3D Active Shutter Eyewear	—	
AUDIO		
Speakers	Full-range x 2 (L, R)	
Number of Speakers	2	
Audio Output	20 W	
Surround Sound	Y	
JACKS		
Integrated ATSC Tuner	Y	
VIERA Image Viewer	Y (JPEG playback)	
HDMI	Input	3 (1 side)
	Support Feature	Audio Return Channel (Input 1)
USB	—	
Analog Audio Input (for HDMI/DVI)	Y	
Composite Video Input	RCA x 1 (common with Component)	
Audio Input (for Video)	RCA x 1 (common with Component)	
PC Input	D-sub 15-pin x 1	
Component Video Input (Y, PB, PR)	RCA x 1 (common with Composite)	
Audio Input (for Component Video)	RCA x 1 (common with Composite)	
LAN Port	—	
Digital Audio Output	1 (5.1 ch)	
CONVENIENCE		
VIERA Link	Y	
VIERA Connect (IPTV)	—	
Easy IPTV	—	
Wireless LAN Adaptor	—	
Universal Dock for iPod	—	
VIERA Tools	Y	
DLNA	—	
Game Mode	Y	
Trilingual Menu (English/Spanish/French)	Y	
Built-In Closed Caption Decoder	Y	
Sleep Off-Timers and Programable Timer (5 programs)	Y	
GENERAL		
Power Supply	AC 110 – 127 V, 60 Hz	
On Mode Average Power Consumption	80 W	
Receiving System	ATSC/ QAM/ NTSC	
Dimensions with stand	Height [in (mm)]	26.3" (666 mm)
	Width [in (mm)]	40.2" (1,021 mm)
	Depth [in (mm)]	11.4" (288 mm)
Dimensions without stand	Height [in (mm)]	24.9" (632 mm)
	Width [in (mm)]	40.2" (1,021 mm)
	Depth [in (mm)]	4.3" (107 mm)
Mass Weight with stand [lbs (kg)]	41.9 lbs. (19.0 kg)	
Mass Weight without stand [lbs (kg)]	37.5 lbs. (17.0 kg)	
Swivel Angle	—	
Tilt Angle	—	
VESA Compatible	Y	
Carton Dimensions	Height [in (mm)]	29.4" (746 mm)
	Width [in (mm)]	50.6" (1,283 mm)
	Depth [in (mm)]	8.8" (223 mm)
Gross Weight [lbs (kg)]	48.5 lbs. (22.0 kg)	
Optional Wall-mounting Bracket Model Numbers	TY-WK3L2RW	

Available at: 

Call: 301-733-0657
Email: sales@networkspectrum.com

Other products available at:
www.networkspectrum.com/gschedule