



OVERVIEW

SPECIFICATIONS

Projection System	DLP DDR DMD XGA x 1
Resolution	1024 x 768 XGA
Brightness	2500 ANSI Lumens (Presentation Mode) Eco-Mode: 2000lm
Contrast Ratio	2000:1 Full On/Off
Aspect Ratio	4:3, Supports 16:9
Projection Lens	F=2.45-2.62, f=18.7-21.5mm 1:1.15 Manual Zoom, Manual Focus
Light Resource	230-Watt High-Pressure Mercury Lamp. Note: Projector lamps contain mercury. Do not throw in trash. Dispose of lamps according to local, state, or federal laws.
Lamp Hours	Approximately 2000 Hours in Normal Mode Approximately 3000 Hours in Eco-Mode
Color Palette	16.7 Million Colors
Projecting Position	Front/Rear, Table/Ceiling
Projection Distance	3.9-33.4', 1.2-10.2m
Image Size	32"-300" diagonal
RGB Signal	SXGA Compression, XGA True, SVGA/VGA Expansion/True
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL_N, PAL_M, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 576p, 1080i, 720p)
Horizontal Synch Range	15 - 80 kHz
Vertical Synch Range	50 - 85 Hz
Audio	Mono 0.5Watt
Input/Output Terminals	RGB (Analog/Digital)/YCbCr/YPbPr: Mini D-Sub 15 pin x 1, Composite Video: RCA x 1, S-Video: Mini DIN 4-Pin x 1, Audio (RGB/Video): 3.5mm Stereo Mini Jack x 1
Other Terminals	Image Viewer: USB (1.0) Port x 1; Wireless/Image Viewer: SD Card Slot x 1
Color	Black
Dimensions	7.7" (W) x 2.3" (H) x 10.3" (L) 195mm (W) x 58mm (H) x 262mm (L)
Weight	4 lbs, 1.8 kg
Power Supply	100-240 VAC at 50/60 Hz
Power Consumption	280 Watts (Normal Mode), 240 Watts (Eco-Mode)

Operating Environment	32-95 °F/5-35 °C
On-Screen Display Languages	English, French, German, Italian, Spanish, Swedish, Korean, Chinese, Japanese
Functions	Quick Start/Unplug and Go, Full-Auto Adjustment, Auto Digital Keystone Correction (vertical: +12/-18 degrees), Digital Zoom, Freeze, Mute, Quick Color Adjustment, ACW (Advanced Color Wheel), Presentation Timer, Security Password
Accessories	Remote Control, CR2025 (3v Lithium battery) for Remote Control x 1, Power Cable (1.8m/6') x 1, RGB Cable (2m/6.5') x 1, Mini Jack to RCA Adapter (3.5 mm Stereo Mini Jack - RCA/6") x2, Soft Carrying Case x 1, User's Manual (CD-ROM), Quick-Start Guide
Warranty	Three Years, Parts and Labor

available at:  **NETWORK Spectrum®**

call: 1-800-655-9565

email: sales@networkspectrum.com