



Samsung 40" 400UX-2 LCD

The Samsung 40" 400UX-2 LCD video wall display features advanced cooling technologies that allow reliable operation 24 hours a day, 7 days a week. With thin 11mm bezels (.43"), you can build virtually seamless video walls up to 5 x 5. The 400UX-2 also has up to 700 cd/m² max brightness, 1080p resolution, and is compatible with our MID40 interlocking assembly kits.

Display

Screen Size	40"
Brightness	700 cd/m ²
Contrast Ratio	3000:1 (DC 30000:1)
Resolution	1920 x 1080
Response time	8
Viewing Angle (Horizontal/Vertical)	178° / 178°
Color Support	16.7 Mil.

Signal input

Video Signal	Analog RGB, DVI -D, Composite, component Video, HDMI, CVBS
Sync. Signal	Separate H/V, Composite, SOG
Connector	D-Sub, DVI-D, CVBS, BNC (Component, PC), HDMI

Power

Power Consumption	230 W
Stand By Power (DPMS)	< 2 W
Type	Internal

Features

Plug & Play	DDC 2B
Mac compatibility	Yes
Multimedia Speakers	10W*2 (Built-in)
Wall-Mount	Mounting Kit Available (WMN - 5770D)
Cabinet Color	Black

Accessory

Quick Setup Guide, Warranty Card, User's Guide, Power Cord, Remote Control, Batteries
Special Features Lamp Error Detection, Temperature Sensor, Built-in Fan, IR In/Out, Video Wall Processor,
MID Interlocking Kit Compatible, RS-232C, PIP, Safety Lock

Dimension

Product Dimension (With stand, WxHxD)	36" x 23" x 12.2"
Product Dimension (Without Stand, WxHxD)	36" x 20.7" x 4.6"
Shipment Dimension (WxHxD)	40" x 25.7" x 12.2"

Weight

Product Weight	46.6 lbs.
Shipment Weight	55.4 lbs.

Stand

Type	Stand Available (STN - L3257D)
------	--------------------------------