



# 460DR-SL

## 46" 1366 x 768 3500:1 Widescreen LCD Display with Cooling Technology



46" High Brightness Professional LCD Window Display (LANDSCAPE) with Samsung Cooling Technology This indoor and outdoor LCD display makes a powerful impact with the advanced technology needed to weather any environment. Get the message across to your customers with an exceptionally high brightness. A variety of customized applications comes with this panel-only solution. Convenient connectivity includes VGA, DVI, BNC, CVBS, S-Video, Component and HDMI. For showcasing the latest menu or this week's movies, this large format display delivers a variety of custom applications like touch screens, built-in speakers, and protected glass.

<b>Technical Specifications</b>
<b>Panel</b>
<ul style="list-style-type: none"> <li>• Diagonal Size:46"</li> </ul>
<ul style="list-style-type: none"> <li>• Type: S-PVA (DID)</li> </ul>
<ul style="list-style-type: none"> <li>• Resolution: 1366 x 768</li> </ul>
<ul style="list-style-type: none"> <li>• Pixel Pitch (H x V): 0.7455 x 0.7455</li> </ul>
<ul style="list-style-type: none"> <li>• Brightness (Typ.): 1500 cd/m<sup>2</sup></li> </ul>
<ul style="list-style-type: none"> <li>• Contrast Ratio: 3500:1</li> </ul>
<ul style="list-style-type: none"> <li>• Viewing Angle (H/V): 178°/178°</li> </ul>
<ul style="list-style-type: none"> <li>• Response Time (G-to-G): 8 ms</li> </ul>
<ul style="list-style-type: none"> <li>• Color Space (CIE1931): 50%</li> </ul>
<b>Connectivity</b>
<ul style="list-style-type: none"> <li>• PC inputs: VGA/DVI/BNC</li> </ul>
<ul style="list-style-type: none"> <li>• Video Inputs: CVBS/S-Video/Component/HDMI</li> </ul>
<b>Power</b>
<ul style="list-style-type: none"> <li>• Power Consumption (Max): 330W</li> </ul>
<ul style="list-style-type: none"> <li>• Power Consumption at Stand-by (Max): 1W (Energy Saving ON)/5W (Energy Saving OFF)</li> </ul>
<ul style="list-style-type: none"> <li>• Power Supply: AC 100 - 240 V (+/-10%), 50/60 Hz</li> </ul>
<b>Mechanical Spec</b>
<ul style="list-style-type: none"> <li>• VESA Mount: 600 x 400 mm</li> </ul>
<ul style="list-style-type: none"> <li>• Weight (Set/Package): 57.3 lbs./67.7 lbs.</li> </ul>
<ul style="list-style-type: none"> <li>• Dimension (W/O Stand): 41.2" x 25.6" x 4.6"</li> </ul>
<ul style="list-style-type: none"> <li>• Packing Dimension: 45.9" x 30.2" x 11.4"</li> </ul>

<ul style="list-style-type: none"> <li>• Bezel Width: 11 mm (Panel)</li> </ul>
<b>Operation</b>
<ul style="list-style-type: none"> <li>• Operating Temperature: TBD</li> </ul>
<ul style="list-style-type: none"> <li>• Humidity: TBD</li> </ul>
<ul style="list-style-type: none"> <li>• MTBF: 50,000 hrs.</li> </ul>
<b>Regulations</b>
<ul style="list-style-type: none"> <li>• Safety: UL, CSA, NOM</li> </ul>
<ul style="list-style-type: none"> <li>• EMC: FCC</li> </ul>
<ul style="list-style-type: none"> <li>• Ergonomics &amp; Environments (option): TCO'95, TCO'99</li> </ul>
<b>Feature</b>
<ul style="list-style-type: none"> <li>• Special Features</li> </ul>
<ul style="list-style-type: none"> <li>• Kit type</li> </ul>
<ul style="list-style-type: none"> <li>• with Air Conditioner or Air Conditioner Guide</li> </ul>
<b>Package Contents</b>
<ul style="list-style-type: none"> <li>• Manuals: Quick Setup Guide, Warranty Card, Users Guide</li> </ul>
<ul style="list-style-type: none"> <li>• Cables: D-sub cable, Power Cord</li> </ul>
<ul style="list-style-type: none"> <li>• Others: Remote Control, Batteries, BNC to RCA Adapter Jack</li> </ul>

Available at:  NETWORK Spectrum®

Call: 301-733-0657

Email: [sales@networkspectrum.com](mailto:sales@networkspectrum.com)

Other products available at:

[www.networkspectrum.com/gsaschedule/](http://www.networkspectrum.com/gsaschedule/)