



# 460DRN-S 46" LCD Display



## Command your audience attention

- RS232C In-Out
- A smart sensor that automatically saves energy.
- Reliable, durable and dust-resistant.
- Save money, save space with built-in speakers.

<b>Panel</b>	<b>Diagonal Size</b>	46"		
	<b>Type</b>	S-PVA(E-DID)		
	<b>Resolution</b>	1,366 x 768		
	<b>Pixel Pitch(mm)</b>	0.7455(H) x 0.7455(V)		
	<b>Active Display Area(mm)</b>	1,018.353(H) x 572.544(V)		
	<b>Brightness(Typ.)</b>	1,500cd/m <sup>2</sup>		
	<b>Contrast Ratio</b>	3,500:1		
	<b>Viewing Angle(H/V)</b>	178/178		
	<b>Response Time(G-to-G)</b>	8ms		
	<b>Display Colors</b>	8bit - 16.7M		
	<b>Color Gamut</b>	72%		
<b>Display</b>	<b>Dynamic C/R</b>	5,000:1		
	<b>H-Scanning Frequency</b>	30kHz - 81kHz		
	<b>V-Scanning Frequency</b>	56Hz - 85Hz		
	<b>Maximum Pixel Frequency</b>	165MHz		
<b>Connectivity</b>	<b>Input</b>	<b>RGB</b>	Analog D-SUB, DVI-D	
		<b>Video</b>	CVBS, HDMI	
		<b>Audio</b>	RCA(L / R), Stereo mini Jack	
	<b>Output</b>	<b>Audio</b>	RCA(L / R)	
		<b>Power Out</b>	5V(for SBB)	
	<b>External Control</b>	RS232C(in / out)		
<b>Power</b>	<b>Type</b>	Internal		
	<b>Power Supply</b>	AC 100 - 240V~ (+/- 10 %), 50/60Hz		
	<b>Power Consumption</b>	<b>On Mode</b>	520 watts(max) / 480 watts(typ)	
		<b>Sleep Mode</b>	5 watts	
<b>Off Mode</b>		5 watts		
<b>Mechanical Spec</b>	<b>Dimension (mm)</b>	<b>Set</b>	1,124.5 x 773.0 x 160.0 (Landscape)	
			678.0 x 1,219.5 x 160.0 (Portrait)	

		<b>Package</b>	1,240.0 x 890.0 x 350.0 (Landscape) 803.0 x 1,330 x 350 (Portrait)
<b>Weight (kg)</b>	<b>Set</b>		48 (Landscape), 47 (Portrait)
	<b>Package</b>		54 (Landscape), 53 (Portrait)
	<b>VESA Mount</b>	600 x 400mm	
	<b>Protection Glass</b>	Yes	
	<b>Media Player Option Type</b>	Internal	
<b>Operation</b>	<b>Operating Temperature</b>	10°C - 40°C	
	<b>Humidity</b>	10 - 80%	
<b>Features</b>	<b>Key</b>	Window display	
	<b>Special</b>	High Brightness, Cross Flow system, Built in Speaker(10 watts + 10 watts), Lamp Error Detection, Anti Retention, Temperature Sensor, RS232C MDC, Magicinfo Pro, Windows XP embedded	
<b>Certification</b>	<b>Safety</b>	UL(USA): UL 60950-1CSA(Canada): CSA C22.2 No. 60950-1 TUV(Germany): EN60950-1NEMKO(Norway): EN60950-1 KC(Korea): K60950-1 CCC(China): GB 4943-2001PSB(Singapore): IEC60950-1GOST(Russia): IEC60950-1, EN55022SIQ(Slovenia): IEC60950-1, EN55022PCBC(Poland): IEC60590-1, EN55022NOM(Mexico): NOM-019-SCFI-1993IRAM(Argentina): IEC60950-1SASO(Saudi Arabia): IEC60950-1	
	<b>EMC</b>	FCC(USA) FCC Part 15, Subpart B class ACE(Europe) EN55022, EN55024VCCI(Japan) V-3(CISPR22) KCC(Korea): KN22, KN24BSMI(Taiwan): CNS13438(CISPR22) C-Tick(Australia): AS / NZS3548(CISPR22) CCC(China): GB 9254-2008, GB 17625.1-2003	
<b>Accessories</b>	<b>Included</b>	Quick Setup Guide, Warranty Card, Application CD, Power Cord, Remote Controller, Batteries	
<b>Media Player</b>	<b>CPU</b>	Athlon X2 Dual-Core 4,450e (2.3GHz)	
	<b>N/B</b>	AMD RS780	
	<b>S/B</b>	AMD SB700	
	<b>GPU</b>	AMD RS780(IGP)	
	<b>FDM/HDD</b>	HDD 40GB	
	<b>Memory</b>	DDR2 1GB	
	<b>Ethernet</b>	Marvell 88E8055 Gigabit LAN	
	<b>Connectivity</b>	<b>USB</b>	5EA
<b>Output</b>		D-SUB(RGB OUT)	
<b>Others</b>		LAN RJ45	

Available at:  NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

[www.networkspectrum.com/gsaschedule/](http://www.networkspectrum.com/gsaschedule/)