

Samsung 460UXn-UD2



The Samsung 46" 460UXn-UD2 commercial-grade LCD video wall display offers reliable 24/7 operation, 12.5mm bezels (.49") for virtually seamless video walls, up to 700 cd/m2 max brightness, 1080p resolution, and compatibility with our MID46 interlocking assembly kits. The 460UXn-UD2 display adds real-time, dynamic content control from a single PC, with up to 125 source PCs and video walls of up to 250 displays.

Display

Screen Size	46"
Brightness	700
Contrast Ratio	4.000:1 (DC 30.000:1)
Resolution	1920 x 1080
Response time	8 ms
Viewing Angle (H/V)	178° / 178°
Color Support	16.7 mil.

Signal input

Video Signal	Analog RGB, DVI -D, Composite, HDMI
Sync Signal	Separate H/V, Composite, SOG
Connector	D-Sub, DVI-D, CVBS, BNC (Component, PC), HDMI

Power

Power Consumption	320 W
Stand By Power (DPMS)	< 5 W
Type	Internal

Features

Plug & Play	DDC 2B
Mac compatibility	Yes
Multimedia Speakers	10 w x 2 (Built-in)
Wall-Mount Mounting Kit	Available (WMN - 5770D)
Cabinet Color	Black

Accessory

Quick Setup Guide, Warranty Card, User's Guide, D-Sub Cable, Power Cord, Remote Control, Batteries, BNC to RCA Adaptor Jack

Special Features

Anti-image retention, Video Wall upto 5X5, Safety Lock, PIP/PBP, RS-232C, Wired Remote IN/OUT, Lamp Error Detection, Temperature Sensor, Built-in Fan, IR In/Out, Video Wall Processor, MID Interlocking Kit Compatible, UD (Ultra-Definition) Software Solution

Dimension

Product Dimension

(With stand, WxHxD) 41.3" x 26.1" x 12.2"

Product Dimension

(Without Stand, WxHxD) 41.3" x 23.7" x 4.65"

Shipment Dimension (WxHxD) 45.2" x 27.8" x 13.0"

Weight

Product Weight 60.9 lbs.

Shipment Weight 71.5 lbs.

Stand

Type Stand Available (STN - L3257D)