



# Now...!

It's time to bring your presentation to life and let it captivate your audience.

## Samsung Digital Presenter **SDP-950DXA/STA**

- 1/3" progressive scan CCD (850,000 pixels)
- Vivid Live Images with 20fps Real Time Motion
- Faster Data Transfer with USB 2.0 PC Interface
- Various External Output Supports - 1 DVI & 2 VGA Support
- Convenient Digital Functions :  
image split, shift, image freeze & rotate,  
3x3 screen display and 8 pictures store
- Powerful 36X Magnification. (12X Optical & 3X Digital)
- Easy to Use GUI & Mouse-Controlled Annotation
- Compact & Light weight Design





SPECIFICATION	DESCRIPTION	SDP-950DXA	SDP-950STA
Optical system	Lens	F=1.5(Wide) ~ 2.1(Tele) f=5.2-66.5, 12x power zoom	
	Shooting Area	Max : 299 x 244mm, Min : 21 x 16mm	
	Zoom	Powered (12x), Digital (3X)	
	Focus	Powered (Auto Focus / Manual)	
Illumination system	Iris	Auto (with fine level adjustment)	
	Upper	Attached to the side arm of the main unit	
Video	Lower	Light box (built-in main unit)	
	Pick-up Device / Effective pixel	1/3" 850,000 pixels PS CCD / 1034(H) x 779(V)	
	Frame rate	20 frame/sec	
	Sync system	Internal sync.	
	VGA output	1024 x 768(XGA) RGB color	
	Video output	C-Video VBS 1.0Vp-p / 75 $\Omega$ Y(unbalance) S-Video Y : 1.0Vp-p / 75 $\Omega$ Y(unbalance) C : 0.286Vp-p / 75 $\Omega$ Y(unbalance)	
	White Balance	Manual / Auto (one touch type)	
	Negative / Positive	Selectable	
	Freeze	built-in	
	Input terminals	VGA : 2	
	Output terminals	VIDEO : 1, VGA : 2, USB : 1, DVI: 1, RS-232C : 1, S-Video : 1, C-Video: 1	
	NTSC / PAL	Selectable	
	Remote controller	Supplied	
	GUI(Graphic User Interface)	Supplied	
	Input selection	3 channels (Internal : 1, External: 2)	
	On-screen display	Available	
	Image freeze	Available	
	Image save	Available (8 frames)	Unavailable
	Image recall	Available (8 frames)	Unavailable
Image divide	Available (2/9 divide)	Unavailable	
Image rotation	Available (90°, 180°, 270°)	Unavailable	
Image transfer to computer	Available (USB : QUAR, HALF, FULL, SCREEN FULL)		
Preset function	Up to 4 user settings		
PC connection	USB	USB 1.1 / 2.0	
	RS-232C	SET control	
	Application software	Viewer software: Windows 98 or higher / Mac OS 10.2 or higher TWAIN Driver for Windows AVI Capture software for Windows	
General	Operating temperature/Humidity	+5°C ~ +35°C, 30% ~ 90%	
	Power	DC12V (Adaptor INPUT: AC100V-240V Free Voltage, 50/60Hz, OUTPUT: 12V, 4.0A)	
	Dimensions	In-use : 25.6(W)" x 22.3(H)" x 16.0(D)" / Storage : 18.8(W)" x 6.0(H)" x 16.0(D)"	
	Weight	10.6 lb	
	Accessories	Suitcase (SDP-950DXA Only), Remote controller, Cables, etc.	

### Rear Panel



### Option



**BAG-950**  
deluxe carrying case  
(Included for SDP-950DXA)

### Dimension

