

# PDG-DHT100L

Active Maintenance Filter, Wireless HD transmission and more.



\*Lens sold separately

**6,500 lumens, and Full HD video for a high brightness and superior image**  
 The PDG-DHT100L answers the growing needs in the digital signage market for use in brighter environments. This bright projector is designed to handle Full HD (1920 x 1080) high quality resolution image projection, it meets the changing needs of the marketplace for more widespread use of high definition input signals. Attention to detail and accuracy in image projection allows use of the projector in more demanding situations, such as specialized design fields or CAD applications. The PDG-DHT100L has two different types of user-changeable color wheels. 6 segments color wheel provides rich color reproduction, 4 segments wheels offers high brightness.

**Dust-resistant sealed optical engine and \*35,000 hour-use 'Active Maintenance Filter', for cleaner and highly durable projection**  
 New, improved, sealed optical engine cooling design prevents dust build-up while maintaining optimal brightness and contrast. The traditional problems of maintaining high projection quality are overcome with the PDG-DHT100L.  
 \* ECO lamp mode

**Various features for versatile installation**  
 Equipped with 'Edge Blending' function that allows what feels like boundary-less images with multi-image display possibilities. Built-in 'Color Matching' function correcting variations in color reproduction when using more than one projector. Capable of projecting two images simultaneously either using built-in picture-in-picture mode or picture-by-picture mode.

**Uncompressed HD DATA WIRELESS transmission optional adapter(Option)**  
 The PDG-DHT100L projector is compatible with an uncompressed HD DATA WIRELESS Transmission System. It allows pure uncompressed data transmission without delays between the video and sound. This wireless technology allows uncompressed data from distances of up to 98-feet from the input source, therefore there is easy set-up for large event halls and other large rooms/theaters.

**24/7 feature "Lamp interval function"**  
 The lamp interval" function can be used to automatically switch the lamp that is turned on to an alternate lamp after a certain period of time in order to reduce the initial lamp deterioration. A user can select from [Off/Auto/200h/500h/1000h/2000h] or 24h" interval time, and rotate each lamp for 24/7 usage.



DLP® and the DLP logo are registered trademarks of Texas Instruments. BrilliantColor™ and DynamicBlack™ are trademarks of Texas Instruments.



PRESENTATION TECHNOLOGIES

21605 Plummer Street  
 Chatsworth, CA 91311  
 Ph: 888-337-1215 (toll-free)  
 Fax 818.717.2719  
 www.sanyoprojectors.com

## Specifications

Resolution	HD 1920 x 1080 (UXGA dot resizing possible)
Brightness (typical)	6,500 ANSI lumens
Contrast Ratio	7,500:1
Panel System	DLP® 1-chip system
Number of Pixels	(2,073,600) 1920x1080 (16:9)
Uniformity	90%
Scanning Frequency	Horizontal: 15-120KHz, Vertical: 48-120Hz, Dot Clock: 230 MHz or less (analog)
Input signal compatibility	UXGA/SXGA+/SXGA/WXGA/XGA/SVGA/VGA/MAC, 1080p-24/25/30/48/50/60, 1080psf-24/25/30, 1080i-50/60, 720p-50/60/575p/480p/575i/480i
Color System	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Zoom/Focus	depends on Lens
Image Size (diagonal)	Minimum 50" - Maximum 600" (Projection distance differs by lens)
Throw Distance	depends on Lens
Throw Ratio	depends on Lens
Up/Down Ratio	Up/Down (6.65:-1 ~ -1:6.65) Left/Right (10.7:1 ~ 1:10.7) depends on Lens
Digital Keystone	V: +/- 30 °, H: +/- 30 °
Digital Zoom	49x - 1/4x
Projection Lamp(s)	330W UHP Lamp x 2
Voltage	100V-240V AC (auto voltage)
Power Consumption	846W (Normal) 758W (Eco1)
Fan Noise	36 dB (Eco1)
BTU Rating	2887 (Normal) 2586(Eco1)
Weight	43.6 lbs
Dimensions	15.75" (w) x 9.55" (h) x 20.61" (d) (including protrusion)
Terminals PC Input/Output	<b>Input 1:</b> Digital video input x 2 ; DVI-D x 1(HDCP compatible), HDMI x 1(Ver 1.3b(Deep color)) Analog RGB input x 1 ; D-sub 15-pin x 1 <b>Input 2:</b> BNC x 5 (RGBHV, VIDEO/Y-Pb/Cb-Pr/Cr), S-video x 1 <b>Input 3:</b> Expansion slot (empty) <b>Input 4:</b> RJ45 LAN x 1, Serial D-sub9 IN x 1 (Expansion slot:POA-MD13NET2)
Terminals Controller input/output, and other	<b>Monitor output :</b> D-sub15 x 1(Analog RGB, Y-Pb/Cb-Pr/Cr, VIDEO) <b>Serial port :</b> D-sub9 IN x 1 / OUT x 1 <b>Wired remote control port :</b> Mini-jack x 1 <b>Service port :</b> USB type B x 1
Replacement	Lamp : 610 343 5336 Remote: 645 099 0199
Included Accessories	Rich color reproduction color wheel (6 Segments) set x 1 High Brightness Color Wheel (4 Segments) set x 1 (Installed) Wireless (wired incl.) remote control x 1 (AA battery x 2) Cable cover 1-type (support cover x 1, cover x 1) Removable power cord x 1, Fixing bracket for power cord x 1 Computer cable (D-sub type) x 1 Real Color Manager Pro (CD-ROM), Instruction manual x 1, Warranty x 1 Lens hole cover x 1 PIN code-locking seal x 1
Optional Accessories	POA-FIL131 – Replacement AMF POA-MD23ADI - DVI/D-sub module POA-MD25VD3 – 5BNC/VIDEO module POA-MD18DVI – DVI module POA-MD16VD1 – 5BNC module POA-MD17SDID – HD&SD – SDI module (SD-SDI not compatible) POA-HDTM01 - HD Wireless Transmitter POA-MD26HDWL - HD DATA WIRELESS receiver board Optional Lenses (see below)

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

Optional Lens Specifications						
	On-Axis Short Fixed	Short Zoom	Short Zoom	STD Zoom	Long Zoom	Ultra Long Zoom
Part No.	LNS-W52	LNS-W51	LNS-W50	LNS-S50	LNS-T50	LNS-T51
Throw Ratio	0.8:1	1.2-1.5:1	1.5-1.8:1	1.8-2.8:1	2.8-5.0:1	4.8-8.0:1

Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/