

2500 LUMENS ● SVGA ● ULTRAPORTABLE PROJECTOR

PDG-DSU30

ULTRAPORTABLE PROJECTOR



DLP®

ULTRA-COMPACT, FULLY PORTABLE SVGA DESIGN

Not much larger than a laptop PC, the PDG-DSU30 weighs less than 5.1 pounds and delivers true SVGA picture quality in a versatile, go-anywhere system.

HIGH BRIGHTNESS AND CONTRAST

A brightness level of 2500 ANSI Lumens and a contrast ratio of 2200:1 make this projector a winner in its category. It's all the quality DLP® technology has become known for.

BETTER CONTROL

The PDG-DSU30 comes with an RS232C control port x1 for advanced projection control.

F2.41 - 2.55 ZOOM LENS

A flexible zoom lens allows for projection setup in both business and home environments. This lens is adjustable to show up to a 300 inch diagonal screen size.

AUTO INPUT SEARCH

This special feature searches, finds and displays incoming source material automatically.

SPECIAL FEATURES

6 Segment color wheel produces vivid colors and versatile go anywhere capability make this a truly portable projector. Also may be ceiling or inverse mounted for enhanced versatility.

ENVIRONMENT FRIENDLY POWER CONSUMPTION IN ECO STANDBY MODE: 1W

The power consumption is reduced in Eco standby mode to 1W.

Resolution	SVGA (800 x 600)	
Brightness (typical)	2500 Lm	
Contrast Ratio (Full on / off)	2200:1	
Image Size	28"-300"	
Aspect Ratio	4:3	
Projection Lamp	180W	
Scanning Frequency	H:31.35-91.1kHz, V:56-85Hz	
Fan Noise	30 dBA (Eco)	
Voltage	100-240V AC (auto voltage) ; 50/60 Hz	
Power Consumption	225W (Eco)	
Input signal compatibility	UXGA/ WXGA/ SXGA/ XGA/ SVGA/VGA/ 480i/480p/576i/576p/720p/1080i/1080p	
Color System	B/D/G/K/K1/L	
Projection Lens (inch)	F 2.41 - 2.55 f=0.86" - 0.95"	
Throw Ratio	1.95 - 2.15:1	
Throw Distance (feet)	3.6' - 43.0'	
Zoom / Focus	Manual	
Digital Keystone Correction	V +/- 15° MAX	
Digital Zoom	4x - 1x	
Speaker Output	2W	
Weight (lbs)	5.1 lbs	
Dimensions (inch) W,H,D	11.3 x 3.4x 7.5 inch	
Replacement Lamp	CHSP8CS01GC01	
Replacement Remote	CH458CS01G001	
Lamp Life * (hours)	Up to 4000h (Eco)	
Input	PC/Video	D-sub 15 x 1 (RGB, Component) Mini DIN 4pin x 1 (S-Video) RCA x 1 (Composite)
	Audio	Stereo mini jack x 1
Output	PC/Video	D-sub 15 x 1 (Monitor out)
Other Feature	Mini DIN 3pin x 1 (RS232C)	
Included Accessories	AC power cord x 1 VGA cable x 1 Owner's manual x 1(CD-ROM) Lens Cap x 1 Remote control x 1(CR2025 battery x 1)	
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product our design and specifications without notice and without incurring any obligations.

* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



PRESENTATION TECHNOLOGIES
21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax: 818-717-2719
www.sanyoprojectors.com



Back Panel

Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/