

4000 LUMENS ● XGA ● ULTRAPORTABLE PROJECTOR

PLC-XU4000

XGA ULTRAPORTABLE PROJECTOR



3LCD



Built-in Network



Closed Caption

HIGH BRIGHTNESS AND COMPACT BODY

The PLC-XU4000 weighs less than 8 pounds and delivers true XGA picture quality in a compact designed package. This new projector leads to a brightness of 4000Lm. It provides brilliant and clear defined image in the conference room or lecture room.

INTELLIGENT LAMP CONTROL SYSTEM OFFERS BRILLIANT IMAGE, HIGH CONTRAST RATIO AND LOWER POWER CONSUMPTION

Thanks to combination of newly developed lamp control and color shift correction technology, Sanyo improves contrast ratio and reduces power consumption without any image degradation. Comparing with conventional models, the PLC-XU4000 is able to reduce power consumption up to 69% in saver mode.

ULTRA-LONG LASTING LAMP AND FILTER

The PLC-XU4000 reduces your total cost of ownership with an ultra long life lamp and filter. The lamp and filter enables 5000H in eco mode an ideal conditions, thanks to a re-designed cooling system, filter size and layout.

COMPLETE EASY AUTO SET UP FUNCTION, SMART AUTO INPUT SEARCH AND AUTO VERTICAL KEYSTONE CORRECTION

PLC-XU4000 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, automatically adjusting for keystone picture distortion. This Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it easy and simple to use.

WIRED LAN (RJ-45) FOR NETWORK PROJECTOR CONTROL

This model is equipped with Wired LAN (RJ-45) that allows you to manage and control the projector via the Network. Providing access to check the projectors operating time of the lamp, control the projector and receive any warning notifications by email. Power ON/OFF and switching of the input signal can also be controlled.

MICROPHONE TERMINAL WITH 10W SPEAKER

The PLC-XU4000 offers an additional feature of a microphone input terminal. Simply connecting the microphone to the terminal, the presenter can use this feature immediately. The projector is equipped with a 10W speaker and therefore there is no need to set-up any amplifier with cables.

CLOSED CAPTION

PLC-XU4000 is Closed Caption compatible.



PRESENTATION TECHNOLOGIES
21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax: 818-717-2719
www.sanyoprojectors.com

Resolution	XGA (1024 x 768)	
Brightness (typical)	4000 Lm	
Contrast Ratio	2000:1	
Image Size	40"-300"	
Aspect Ratio	4:3	
Projection Lamp	245W	
Scanning Frequency	H:15-100kHz, V:50-100Hz	
Fan Noise	29 dBA (Eco)	
Voltage	100-240V AC (auto voltage) ; 50/60 Hz	
Power Consumption	121W (Saver), 184W(Eco2), 322W(Normal)	
Input signal compatibility	WUXGA, UXGA, SXGA+, WXGA+, XGA, SVGA, VGA MAC, 1080i 50/60, 1035i, 720p, 480p/i, 575p/i	
Color System	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N	
Projection Lens (inch)	F 1.60- 1.76, f=0.88" - 1.05"	
Throw Ratio	1.73 - 2.08 : 1	
Throw Distance (feet)	4.6' - 41.6'	
Zoom / Focus	Manual	
Up / Down Ratio	9 : 1	
Digital Keystone Correction	V +/- 30° (Auto keystone +/- 20°)	
Digital Zoom	16x - 1/4x	
Speaker Output	10W	
Weight (lbs)	7.3 lbs	
Dimensions (inch) W,H,D	13.8" x 3.8" x 10.3"	
Replacement Lamp	# 610 352 7949	
Replacement Remote	# 645 099 3213	
Lamp Life * (hours)	5000h (Eco)	
Input	PC/Video	D-sub 15pin x1 (RGB, Component) D-sub 15pin x1 (RGB, Monitor out) RCA x1 (Composite) Mini Din 4pin x1 (S-Video)
	Audio	Stereo mini jack x 2 (Audio input, Mic input in common) RCA x2 (R/L, mono)
Output	PC/Video	D-sub 15 x1 (in common)
	Audio	Stereo mini jack x 1
Other Feature	RJ-45 x1 (LAN) Dsub 9pin x1 (RS232C)	
Included Accessories	Power cord VGA cable Remote control AAA Battery x2	Quick reference guide Owner's Manual(CD-ROM) PIN code Label
	Optional Accessories	POA-CACOMPVGA (Component -VGA cable) POA-CAVGAS (S-Video -VGA cable) POA-CACVCL2 (Soft carry case)
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



Back Panel

Available at: NETWORK Spectrum®

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/