

CD5230

**52" SLIM BEZEL FULL HD 1080P
COMMERCIAL LCD DISPLAY**

Grand Format for Large, Crisp Digital Signage Images

ViewSonic's 52" CD5230 Commercial Display is designed for use in educational, retail, public and commercial signage applications. Full 1080p resolutions provides a clear view in any installation. Generous screen size and slim bezel make your message stand out in a big way. Multiple connectivity and resolutions provide you with lots of options for showing a diverse set of digital signage content; from movies, to internet pages, PowerPoint, Flash, and much more with ultimate HD clarity. Display your vivid graphics and stunning video beautifully with this larger, bright and high contrast screen.



- > 1080p 8ms panel for vibrant video and crisp images
- > High brightness and contrast ratio
- > RS-232 daisy-chain capable
- > VGA and DVI inputs/outputs for flexible connectivity and control
- > Remote and panel control lock out
- > Installation options include stand or VESA® wall mount

Shown with optional stand.

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

ViewSonic®
See the difference® 

CD5230 52" SLIM BEZEL FULL HD 1080P COMMERCIAL LCD DISPLAY



Shown with optional stand.

LCD	Type	52" color TFT active matrix, wide LCD	
	Display Area	45.3" horizontal x 25.5" vertical; 51.9" diagonal	
	Optimum Resolution	1920x1080	
	Contrast Ratio	2500:1 (typ)	
	Viewing Angles	178° horizontal, 178° vertical	
	Response Time	8ms	
	Light Source	Long life, 50,000 hrs. (typ)	
	Brightness	700 cd/m2 (typ)	
	Aspect Ratio	16:9	
	Panel Surface	Anti-glare, hard coating (3H)	
INPUT	Video Input	HDMI, DVI, component, VGA	
	Video Output	VGA, component, DVI	
	Control Input/Output	RS-232	
AUDIO OUTPUT	Amplifier	2-watt	
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p	
CONNECTOR	Analog	15-pin mini D-sub (VGA)	
	Digital	HDMI, DVI	
	Power	3-pin plug	
POWER	Voltage	AC 100-240V (universal), 50-60Hz	
	Consumption	360W (typ)	
CONTROLS	Panel	Power, Exit, +, -, Menu/Enter	
	Picture	Picture mode, contrast, brightness, color temperature, temperature adjust, sharpness	
	VGA Setting	Auto adjustment, clock, phase, sharpness, H. position, V. position	
	OSD Setting	Languages, OSD H. position, OSD V. position, OSD timer	
	Input	VGA, DVI, HDMI, YPbPr	
	Audio	Volume, mute, audio source	
	Special	Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset	
	Diagnostic	Thermal, back light, ambient, 5V detect, 12 detect	
	OPERATING CONDITIONS	Temperature (landscape)	32-104°F (0-40°C)
		Temperature (portrait)	41-95°F (5-35°C)
Humidity		20-80% (non-condensing)	
DIMENSIONS (W x H x D)	Physical with stand (optional)	47.1" x 29.1" x 8.8" (1197mm x 740mm x 223mm)	
	Physical without stand	47.1" x 27.4" x 5.0" (1197mm x 693mm x 126mm)	
WEIGHT	Net with stand (optional)	88.9 lb. (40.3 kg)	
	Net without stand	83.8 lb. (38.0 kg)	
	Gross without stand	99.21 lb. (45.0 kg)	
VESA® MOUNT		400mm x 200mm	
REGULATIONS		UL/FCC-B	
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.	
PACKAGE CONTENTS		LCD display, power cable, remote control with batteries, Quick Start Guide	
WARRANTY		Three-year limited warranty on parts, labor and backlight	

Complete Your Digital Signage Solution

Add a network media player and digital signage software.

Media Players

- NMP-550 (RISC-based)
- NMP-600 (X-86-based)
- NMP-610 (X-86-based)
- NMP-700 (X-86-based)

Software

- ViewSonic's Signage Manager Express
- VMS 2.0
- FriendlyWay Composer Software
- Best Wave *DisplayIt!* Software



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [15056-00B-06/10] CD5230-1

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com