

VG1932wm-LED

19" WIDE LED DISPLAY

WITH HEIGHT ADJUST, SPEAKERS
AND ENERGY STAR® 5.0

Planet-friendly. Picture perfect.

ViewSonic's new VG1932wm-LED backlight LCD is the newest addition to our green-line of LCD monitors. With Mega DCR at 10,000,000:1 you get true-to-life picture depth and clarity in any room. WLED backlight automatically detects image signal and intelligently controls backlight brightness — making the black, pure black in a dark scene and the white, "whiter" in a bright environment. It also automatically adjusts gray level and enhances the LCD monitor's gray level performance range. Ergonomic design with height adjust, swivel and tilt, integrated speakers, DVI input, and Windows 7 certification make the VG1932wm-LED the best choice for both corporate and education customers.



AMAZING GAMES AND HD CONTENT

- > Uses 50% less power
Without compromising your viewing quality and has eco-friendly mercury free WLED backlight.
- > Ergonomic design with height adjust, swivel and tilt functions
- > DVI and VGA inputs for diverse connectivity
- > Integrated speakers for multimedia applications
- > Dynamic contrast ratio at 10,000,000:1
For true-to-life picture depth and clarity in any room.



ViewSonic®
See the difference® 

VG1932wm-LED

19" WIDE LED DISPLAY WITH WITH HEIGHT ADJUST, SPEAKERS AND ENERGY STAR® 5.0



LCD	Type	19" Wide Color TFT Active Matrix LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19.0" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	1000:1 (typ); 10,000,000:1 (dynamic)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m ² (typ)
VIDEO INPUT	Panel Surface	Anti-glare
	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 24~82kHz, F _V : 50~75Hz
COMPATIBILITY	Sync	H/V separated (TTL), composite sync-on-green
	PC	VGA up to 1440x900 non-interlaced
CONNECTOR	Mac®*	Power Mac™ G3/G4/G5 up to 1440x900
	Analog	15-pin mini D-sub (VGA)
AUDIO	Digital	DVI-D
	Power	3-pin AC plug (CEE22)
	Speakers	1.5x2W
POWER	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	17W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OSD	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K, default, user color - RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
ERGONOMICS	Tilt	Down 5°, Up 20°
	Swivel	360°
	Height Adjust	0-80mm
OPERATING CONDITIONS	Temperature	32~104° F (0~40° C)
	Humidity	10~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	18.1" x 17.1" x 9.1" (460mm x 434mm x 230mm)
	Physical without stand	18.1" x 13.8" x 2.4" (460mm x 352mm x 61mm)
	Packaging	21.7" x 20.0" x 10.8" (550mm x 506mm x 274mm)
WEIGHT	Net with stand	11.5 lb. (5.0 kg)
	Net without stand	8.1 lb. (4.0 kg)
	Gross	18.0 lb. (8.1 kg)
VESA® MOUNT REGULATIONS	75mm x 75mm	
POWER MANAGEMENT	UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, GS (covers GS), ERGO (ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, MIC (KCC), WEEE, RoHS, TCO, EPEAT Gold	
PACKAGE CONTENTS	Meets MPR II and ENERGY STAR® standards	
WARRANTY	LCD display, power cable, VGA video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide and drivers)	
	Three-year limited warranty on parts, labor and backlight.	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Available at: **NETWORK Spectrum®**

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/

ViewSonic®
See the difference® 