

# VG2236wm-LED

## 22" (21.5" VIEWABLE) WIDESCREEN LED MONITOR

WITH HEIGHT ADJUST, SPEAKERS  
AND ENERGY STAR® 5.0

## Planet-friendly. Picture perfect.

The VG2236wm-LED is one of two new members of ViewSonic's new VG36-LED family. Its 22" (21.5" viewable) display with a native 1920x1080 resolution is big enough to replace dual-monitor setups. What makes it even more appealing is the LED backlight for up to 50% energy savings. Monitor is also fully ergonomic with 90° pivot, height adjust, swivel and tilt. The slim bezel design coupled with hidden stereo speakers make VG2236wm-LED a space saver. You can put it on your desk or mount on your wall or on any VESA compliant monitor stand. With Viewsonic's strongest pixel performance guarantee and 3-year limited warranty, you will have peace of mind in your investment.



### AMAZING GAMES AND HD CONTENT


- > **Up to 50% energy saving with LED backlight**  
Without compromising your viewing quality and has eco-friendly mercury free LED backlight.
- > **Multi-functional base design (360° swivel and height adjust)**  
VESA compliant wall-mount interface and detachable base for ergonomic flexibility with pivot, 5.3 height, tilt and 360° swivel adjustments.
- > **OptiSync® digital/analog inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Multimedia enhanced**  
Stereo speakers provide clear and rich sound.
- > **MEGA dynamic contrast ratio at 20,000,000:1**  
For true-to-life picture depth and clarity in any room.
- > **Widescreen aspect ratio with 1920x1080 resolution**  
The widescreen aspect ratio allows you to view Full HD content in its native format with no stretching or distortion.
- > **Wall mountable design**  
100mm x 100mm VESA compliant



**ViewSonic®**  
See the difference® 

# VG2236wm-LED

22" (21.5" VIEWABLE) WIDESCREEN LED MONITOR WITH  
HEIGHT ADJUST, SPEAKERS AND ENERGY STAR® 5.0



<b>LCD</b>	Type	22" (21.5" viewable) Wide Color TFT Active Matrix LCD
	Display Area	18.8" horizontal x 10.6" vertical; 21.5" diagonal
	Optimum Resolution	1920x1080
	Contrast Ratio	1000:1 (typ); 20,000,000:1 (dynamic)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m <sup>2</sup> (typ)
<b>VIDEO INPUT</b>	Panel Surface	Anti-glare, hard-coating (3H)
	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 24~83kHz, F <sub>V</sub> : 50~75Hz
<b>COMPATIBILITY</b>	Sync	H/V separated (TTL), composite sync-on-green
	PC	VGA up to 1920x1080 non-interlaced
<b>CONNECTOR</b>	Mac®*	Power Mac™ up to 1920x1080
	Analog	15-pin mini D-sub (VGA)
<b>AUDIO</b>	Digital	DVI-D
	Audio	3.5 mm audio in
	Power	3-pin plug (CEE22)
<b>POWER</b>	Speakers	2x2W
	Voltage	AC 100~240V (universal), 50/60Hz
<b>CONTROLS</b>	Consumption	22W (typ)
	Basic	Power, 1, down, up, 2
<b>ERGONOMICS</b>	OSD	Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI), Audio adjust (Volume mute), Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off), Memory Recall
	Tilt	Down 5°, Up 20°
	Swivel	360°
	Height Adjust	0-135mm
	Pivot	0-90°
<b>OPERATING CONDITIONS</b>	Temperature	32~104° F (0~40° C)
	Humidity	20~90% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical with stand	20.52" x 16.48" x 9.42" (521.21mm x 418.63mm x 239.2mm)
	Physical without stand	20.52" x 12.66" x 2.02" (521.21mm x 321.71mm x 51.5mm)
	Packaging	23.46" x 19.01" x 6.81" (596mm x 483mm x 173mm)
<b>WEIGHT</b>	Net with stand	9.7 lb. (4.4 kg)
	Net without stand	7.5 lb. (3.4 kg)
	Gross	15.4 lb. (7.0 kg)
<b>WALL MOUNT</b>	VESA® 100mm x 100mm	
<b>REGULATIONS</b>	UL, CUL, FCC-B (ICES), CB, CE, CES-003B, ISO13406-2, TUV/GS, ERGO, TUV-S, NOM, GOST-R, HYGIENIC (20 copies), CCC, BSMI, PSB, C-TICK, MIC(KCC), SASO, WEEE, RoHS, SASO, Ukraine, TCO, EPEAT Gold	
	<b>POWER MANAGEMENT</b>	ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>	LCD display, power cable, DVI cable, audio cable, Quick Start Guide ViewSonic Wizard CD (User Guide and drivers)	
<b>WARRANTY</b>	Three-year limited warranty on parts, labor and backlight.	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Available at: **NETWORK Spectrum®**

Call: 301-733-0657

Email: [sales@networkspectrum.com](mailto:sales@networkspectrum.com)

Other products available at:

[www.networkspectrum.com/gsaschedule/](http://www.networkspectrum.com/gsaschedule/)

**ViewSonic®**  
See the difference®