

Multifunction versatility in an outstanding projector.

ViewSonic's PJ1173 delivers maximum impact for large-venue presentations. With 5,000 LUMENS and 1000:1 contrast ratio (typ), this PREMIUM PROJECTOR is ideally suited for conference rooms, lecture halls, religious sanctuaries and boardrooms. The PJ1173 is full-featured with native XGA 1024x768 resolution, advanced image processing, manual lens shift, horizontal and vertical (auto) keystone correction, and HDMI input to support up to 1080p signals. The image reversing function offers versatile installation options. Network connectivity allows you to REMOTELY CONTROL AND MANAGE YOUR PROJECTOR and the 4x4-watt SRS® WOW STEREO SPEAKERS give your presentations powerful sound. The security bar and PIN lock guard against theft and unauthorized use. The PJ1173 is the full-featured choice for dynamic presentations and smooth video entertainment in large venues.

PJ1173

HIGH BRIGHTNESS MULTIMEDIA PROJECTOR

WITH NETWORK CONTROL



RAISING THE BAR ON YOUR PRESENTATIONS

- > **Ultimate video source flexibility**
Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.
- > **Network control through RJ-45**
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.
- > **Enhanced security features**
PIN lock feature prevents unauthorized use. Kensington® security lock and a security bar allow you to secure the projector to deter theft.
- > **The perfect image in any setting**
Digital horizontal and vertical (auto) keystone correction, manual lens shift, and optical zoom ensure the perfect image in any room.
- > **Superior 16-watt stereo sound**
Four 4-watt speakers with SRS® WOW technology for panoramic 3D sound.
- > **Easy maintenance**
Easy access to the lamp and filter covers even when the projector is mounted.
- > **Optional lenses make installation flexible**
Easy-to-install lens options allow you to project in rooms of virtually any size.
- > **3+1+1 warranty**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® Service and one-year limited lamp warranty.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic® 
See the difference®

PJ1173

HIGH BRIGHTNESS MULTIMEDIA PROJECTOR WITH NETWORK CONTROL



Optional Accessories

- Replacement lampRLC-038
- Extended Express Exchange®PRJ-EE-10-03
- Universal ceiling mount kitWMK-005
- Fixed short throw lensLEN-003
- Short throw zoom lensLEN-004
- Long throw zoom lensLEN-005
- Ultra long throw lensLEN-006
- Wireless G Presentation Gateway ...WPG-150



ISO 9001:2000
FM 40187

ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

PROJECTOR	Type	0.8" Poly-Si TFT with micro-lens
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus, manual lens shift
	Zoom Factor	1.2
	Keystone	Auto-vertical ± 40°, horizontal ± 20°
DISPLAY	Size	30"– 350" (diagonally)
	Throw Distance	35"– 425"
	Throw Ratio	1.5~1.8:1
	Lamp	275W, 2,000 hours*
	Brightness	5,000 ANSI lumens
	Contrast Ratio	1000:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	4x4-watt with SRS® WOW technology
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 575i, 720p, 1080i, 1080p)
	Frequency	F _H : 31–92kHz; F _V : 56–120Hz
COMPATIBILITY	PC	Analog: from VGA up to UXGA (compressed)
	Mac®*	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	Analog RGB: DB-15 (x2), Digital RGB:M1-D
	RGB (output)	DB-15 (x1)
	HDMI	HDMI 1.3 with audio (x1)
	RGB-BNC	BNC-5 (x1 set)
	Wireless Remote Control	IR (x3)
	Mouse Control	VIA M1-D
	Composite Video (input)	RCA-3 jack (x1 set)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	RCA jack (x1 set)
	Audio (input)	3.5mm stereo mini-jack (x2) for RGB, RCA L/R jack (x1 set)
	Audio (output)	3.5mm stereo mini-jack (x1)
	RS-232	9-pin D-sub (x1)
	Network	RJ-45 (x1)
	POWER	Voltage
Consumption		460W (typ)
CONTROLS	Basic	Standby, menu, input, reset, H/V keystone, search, picture mode
OPERATING CONDITIONS	Temperature	32–95°F (0–35°C)
	Humidity	10–85% (non-condensing)
	Altitude	0–12,000 feet
NOISE LEVEL	Normal	39 dB (typ)
	Whisper Mode	33 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	418mm x 139mm x 319mm
	Physical (in.)	16.5" x 5.5" x 12.6"
WEIGHT	Net	15.8 lb. (7.1 kg)
	Gross	25.6 lb. (11.6 kg)
REGULATIONS		UL 60950, C-UL, FCC-B, TUV/GS, CB, CE, C-TICK, GHOST, NOM, CCC, PSB, RoHS
OTHER		Lens shift, progressive scan, PIN lock, network control, anti-theft security bar, daylight mode, 16-watt speakers, optional lenses, active iris, eShot, adjustable fan speed, mouse with laser pointer
PACKAGE CONTENTS		Projector, power cords, VGA cable, RCA video cable, wireless remote control, lens cap, ViewSonic Wizard CD, Quick Start Guide
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp**

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com