

PJD2121

ULTRA-PORTABLE PROJECTOR
WITH BrilliantColor™ TECHNOLOGY

Our Best In Portability

The new ViewSonic® PJD2121 compact portable projector leaves nothing behind but the weight. Brilliant images, produced at 400 lumens with a contrast ratio of 1800:1, ensure your presentation will always shine. Texas Instruments' BrilliantColor™ technology creates pictures true to life. Using multiple picture modes you can create a presentation that will be entertaining and memorable. It supports both 720p and 1080i HD formats. The bottom load lamp and filter-less design provide for easy maintenance and low total cost of ownership. This easy to pack and go device is light weight – just over 2 pounds – and is ready to perform anywhere you take it.



PERFORMANCE YOU TAKE WITH YOU

- > **Compact portable projector**
With a small profile, only 8" x 4 ¾" x 2 ½", this projector is perfect for people on the go.
- > **Super light weight for ultimate mobility**
At just over 2 pounds this projector can effortlessly be carried in briefcase or travel bag.
- > **BrilliantColor™ technology**
Latest BrilliantColor™ technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.
- > **Short throw displays a 60" crisp image from just 4 feet**
Just right for small spaces or small groups.
- > **ViewMatch™ quick key for optimal color**
Make adjustments from the remote control for quick and accurate color corrections.
- > **Off-to-Go feature**
The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.
- > **Supports HD signals including 720p and 1080i**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJD2121

ULTRA-PORTABLE PROJECTOR WITH BrilliantColor™ TECHNOLOGY



| | | |
|-------------------------|-------------------------|--|
| PROJECTOR | Type | 0.55" Digital Micromirror Device (DLP®) |
| | Pixel Format | 800x600 SGVA |
| | Lens | Manual focus |
| | Zoom Factor | Fixed optical |
| | Keystone | Vertical ± 30° |
| DISPLAY | Size | 35"–150" (diagonally) |
| | Throw Distance | 28"–120" |
| | Throw Ratio | 1.0:1 |
| | Lamp | 50W, 2,000 hrs. normal |
| | Brightness (max) | 400 ANSI lumens |
| | Contrast Ratio | 1,800:1 |
| INPUT SIGNAL | Computer and Video | RGB analog, NTSC, HDTV (480i, 480p, 576i, 576p, 720p, 1080i) |
| | Frequency | F _H :15–82kHz; F _V :50–85Hz |
| | COMPATIBILITY | PC Analog: from VGA up to SXGA (scaled) Mac®† Analog: up to SXGA |
| CONNECTOR | RGB (input) | 15-pin HD, D-sub |
| | Component Video (input) | RCA jack x1 set |
| POWER | Voltage | 90–264vac, 50/60Hz (auto switching) |
| | Consumption | 90W (max) |
| CONTROLS | Basic | Standby/on, input, menu |
| | OnView® | Display mode, brightness, contrast, keystone, aspect ratio, blank screen, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (pan and scan, magnify, auto source, select, lamp hours, lamp reset, factory reset) |
| OPERATING | Temperature | 32–104°F (0–40°C) |
| CONDITIONS | Humidity | 10–85% (non-condensing) |
| | Altitude | 0–10,000 ft. |
| NOISE LEVELS | Normal | 31 dB (typ) |
| DIMENSIONS | Physical (W x H x D) | 8.1" x 4.7" x 2.6" (205mm x 120mm x 65mm) |
| WEIGHT | Net | 2.16 lb. (0.98 kgs) |
| | Gross | 5.5 lb. (2.5 kgs) |
| REGULATIONS | | UL/cUL, FCC-B, CE, CB, CCC, NOM, ICES 003, IRAM, TUV/GS, GOST-R, HYGIENIC, SASO, UKrSEPRO, RoHS |
| RECYCLE/DISPOSAL | | The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. |
| PACKAGE CONTENTS | | Projector, power cable with adapter, VGA cable, remote control, soft case, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide) |
| WARRANTY | | 3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1-year free Express Exchange® service* |

Optional Accessories

- Replacement lamp..... RLC-052
- Extended Express Exchange® PRJ-EE-03-03
- Wireless G Presentation Gateway WPG-350



Available at: **NETWORK Spectrum®**

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/

ViewSonic®
See the difference® 